

SUBMITTAL DATA SHEET

Series Name: Hyper Heat AHU Series
Model Number: CCOXHB24V36HP/CCOXHBAH24V36



Air Handler Heat Pump System

Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:



INDOOR SPECIFICATION

ESP(in.W.G)	0-0.8
Indoor Air Flow (Turbo/H/M/L/Si) (CFM)	1189.0 / 1083.0 / 971.2 / 865.2 / 865.2
Indoor Noise Level (Turbo/H/M/L/Si) (dBA)	49/48.0/45.5/25.5/25.5
Dimensions W×D×H (inches)	21.02 x 21.02 x 49.02
Package W×D×H (inches)	26.57 x 24.41 x 52.56
Net/Gross Weight lbs.	129.41/153.88

OUTDOOR SPECIFICATION

Compressor Type	TWIN-ROTARY
Compressor Model	EKPQ420D1UMUA
Refrigerant	R454B
Refrigerant Oil Charge(mL)	1460
Refrigerant Oil	VG75
Outdoor Air Flow (Max) (CFM)	3001.8
Outdoor Noise Level (dBA)	62.5
Dimensions W×D×H (inches)	38.58 x 16.34 x 38.39
Package W×D×H (inches)	45.08 x 19.68 x 42.52
Net/Gross Weight lbs.	204.15/235.23

EFFICIENCY

Cooling		Heating	
SEER2	17.4	HSPF2-4	10.2
EER2	11.7	COP	3.60

COOLING PERFORMANCE (Btu/hr)

Rated Capacity	36000
Min/Max Capacity	9700~42000
Moisture Removal(L/h)	3.4
Standard Operating Range(°F/°C)	-22~122(-30~50)
Rated Cooling Conditions:	Indoor: 80°F DB/67°F WB Outdoor: 95°F DB/75°F WB

HEATING PERFORMANCE (Btu/hr)

1. @ 47°F Rated	37000
2. @ 47°F Min/Max Capacity	11000~48000
3. @ 17°F Rated	31800
4. @ 5°F Rated: Capacity / COP	39000/1.9
5. @ 5°F Max: Capacity	39000
Standard Operating Range(°F/°C)	-22~75(-30~24)
1. Rated Heating Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 47°F DB/43°F WB
2. Rated Heating Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 17°F DB/15°F WB
3. Heating Conditions, Compressor Operating at Max. Frequency	Indoor: 70°F DB/60°F WB Outdoor: 5°F DB/5°F WB


ELECTRICAL

Indoor Power Supply	115/208/230V,60Hz,1Ph
Indoor MCA 115V/(208/230V)	8.0/6.0
Indoor MOP	15
Outdoor Power Supply	208/230V,60Hz,1Ph
Outdoor MCA	29
Outdoor MOP	30
Communication Wiring	AWG 20-2
Compressor RLA	20.5
Outdoor Fan Motor RLA	2.4
Outdoor Fan Motor W	250
Indoor Fan Motor RLA	4.5
Indoor Fan Motor W	375
System Power Input @ Cooling (W)	3076(820 ~ 4440)
System Power Input @ Heating (W)	3012(665 ~ 4370)
MCA: Min. circuit amps (A)	MOCP: Max. over current protection (A)
RLA: Rated load amps (A)	W: Fan motor rated output (W)

PIPING

Throttle type(Indoor)	EXV
Throttle type(Outdoor)	EXV
Liquid Size	9.52mm(3/8in)
Gas Size	19mm(3/4in)
Max. Piping Length(ft/m)	246(75)
Max. Height Difference(ft/m)	98.4(30)
Max. Pre-charged Length(ft/m)	24.6(7.5)
Refrigerant Pre-charged Amount(oz/kg)	126.99(3.6)
Additional Charge (oz/ft)/(g/m)	0.7(65)
Connection Method	Flared


Indoor Unit Dimension




Dimensions		Model		18k/24k		30k/36k		48k/60k	
				inch	mm	inch	mm	inch	mm
A	Model Height			45	1143	49	1245	53	1346
B	Model Width			17-1/2	445	21	534	24-1/2	622
C	Supply Air Opening Width			15-5/8	397	19-1/8	486	22-5/8	575
D	Return Air Opening Width			15-1/8	384	18-5/8	473	22-1/8	562
E	Model Depth			21	534	21	534	21	534
F	Supply Air Opening Depth			10-1/4	260	10-1/4	260	10-1/4	260
G	Return Air Opening Depth			18-3/4	476	18-3/4	476	18-3/4	476
H	Supply Air Opening Clearance			15/16	24	15/16	24	15/16	24

I	Return Air Opening Side Clearance	1-1/4	32	1-1/4	32	1-1/8	28
J	Return Air Opening Front Clearance	1-1/2	38	1-5/8	41	1-5/8	41
K	Return Air Opening Back Clearance	5/8	16	5/8	16	3/4	19

Outdoor Unit Dimension




Installation Instruction For Outdoor Unit



☒ Meets all spatial requirements shown in Installation Clearance Requirements above.

Fan Performance For Indoor Unit



External static pressure (in.w.c.)

Features

- Multi-position installation: horizontal(left or right), vertical(up or down)
- Aluminum Coil
- Constantly Air Flow system up to 0.80 In.W.G
- 1 inch R4.2 fiberglass free insulation reduces condensation and boosts efficiency(optional)
- Optional Auxiliary heat kit up to 25kW
- Easy Maintenance
- Multiple control options available:
 - Two way communication wired controller:120N(X6)
 - Two way communication wired controller with built-in WiFi:120N(X6W)
 - Wireless remote controller
 - Third-Party 24V Thermostat
- Adaptive Control System
- High efficiency up to 19 SEER2, 12.5 EER2, 10.3 HSPF2
- 100% heat output at -4F*
- Chassis heater and crankcase heater equipped as standard

* For 36K model, rated cooling capacity/heating capacity at -4F=100%