

R454b
Refrigerant

SUBMITTAL DATA SHEET

Series Name: Multi Zone Indoor Unit Ceiling Floor
Model Number: CCOXHBFC18



Heat Pump System

Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:



Item	Unit	Specification
Performance Data		
Cooling Capacity*	Btu/h	18,000
Heating Capacity*	Btu/h	18,000
Design Pressure	PSIG	550 / 340
Refrigerant Type	-	R454b
Liquid Side	inch(mm)	1/4" (6.35mm)
Gas Side	inch(mm)	1/2" (12.7mm)
Drain Pipe Size	inch(mm)	1" (25mm)
Indoor Operation Range of Cooling	Deg.°F (°C)	60°F~90°F (16°C~32°C)
Indoor Operation Range of Heating	Deg.°F (°C)	32°F~86°F (0°C~30°C)
Electrical		
Normal Operational Voltage	V, Ph, Hz	208/230V, 1Ph, 60Hz
Voltage Range	V	187-253
Connection Wiring	-	AWG 14/4
MCA	A	1.9
Indoor Fan Motor Model	-	ZKFN-90-8-1
Indoor Fan Motor Output	W	90
Indoor Fan Motor RLA	A	1
Indoor Fan Motor Speed(Hi/Mi/Lo)	r/min	950 / 850 / 750
Air Flow & Noise Level		
Indoor Air Flow (H/M/L)	CFM	577 / 547 / 486 / 421 / 421
Indoor Noise Level (H/M/L)	dB(A)	45 / 43 / 40 / 31 / 29
Dimension (W×D×H)	inch	42 x 26-5/8 x 9-1/4
	mm	1068 × 675 × 235
Package (W×D×H)	inch	45-1/8 x 29-3/4 x 12-1/2
	mm	1145 × 755 × 318
Net Weight / Gross Weight	lbs	58 / 71

Net weight / Gross weight	kg	26.5 / 32.0
---------------------------	----	-------------

*Standard capacity of indoor unit is for reference, capacity varies based on Multi-zone system combinations.

Indoor Unit Dimension

Unit: inch (mm)

The technical drawings illustrate the indoor unit from three perspectives: front, side, and top. The front view shows a rectangular unit with a horizontal grille and a control panel on the right side. Dimension A represents the width, B represents the height, and C represents the depth. The side view shows the unit's profile, highlighting its depth (C) and height (B). The top view shows the unit's layout from above, with dimension D representing the width across the top. The unit is shown with a standard wall-mounting bracket.

Model	A	B	C	D
18K~24K	42	26-5/8	9-1/4	38-3/4
36K~60K	65	26-5/8	9-1/4	61-5/8