

SUBMITTAL DATA SHEET



Series Name: Slim Duct Hyper Heat Series
Model Number: CCOXHBSZ60CHP/CCOXHBSD60

Slim Duct Heat Pump System

Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:



INDOOR SPECIFICATION

Indoor Air Flow (Turbo/H/M/L/Si) (CFM)	001.2 / 1706.9 / 1412.6 / 1118.3 / 1118.
Indoor Noise Level (Turbo/H/M/L/Si) (dBA)	52/52/48/42/41
Indoor static pressure range(in.w.g.)	0-0.8
Dimensions W×D×H (inches)	55.12 x 31.50 x 14.96
Package W×D×H (inches)	62.99 x 36.02 x 17.52
Net/Gross Weight ibs	161.38/178.13

OUTDOOR SPECIFICATION

Compressor Type	TWIN-ROTARY
Compressor Model	EKPQ440D1UMUB
Refrigerant	R454B
Refrigerant Oil Charge(mL)	1300ml
Refrigerant Oil	7.3
Outdoor Air Flow (Max) (CFM)	4237.9
Outdoor Noise Level (dBA)	63.0
Dimensions W×D×H (inches)	37.48 x 16.34 x 52.48
Package W×D×H (inches)	43.11 x 19.49 x 58.27
Net/Gross Weight ibs	230.38/261.69

EFFICIENCY

Cooling		Heating	
SEER2	15.8	HSPF2-4	10.4
EER2	10.2	COP	3.74

COOLING PERFORMANCE (Btu/hr)

Rated Capacity	55000
Min/Max Capacity	14200~60000
Moisture Removal(L/h)	3.63
Standard Operating Range(°F/°C)	-22~122(-30~50)
Conditions:	Indoor: 80°F DB/67°F WB Outdoor: 95°F DB/75°F WB

HEATING PERFORMANCE (Btu/hr)





1. @ 47°F Rated	60000
1. @ 47°F Min/Max Capacity	11200~66000
2. @ 17°F Rated	45000
3. @ 5°F Rated: Capacity / COP	53500/2.10
3. @ 5°F Max: Capacity	53500
Standard Operating Range(°F/°C)	-22~75(-30~24)
1. Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 47°F DB/43°F WB
2. Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 17°F DB/15°F WB
3. Conditions	Indoor: 70°F DB/60°F WB Outdoor: 5°F DB/5°F WB

ELECTRICAL

Power Supply	208/230V,60Hz,1Ph
System MCA	44.00
Connection Wiring	14#x3
System MOC	45
Compressor RLA	26.8
Outdoor Fan Motor RLA	2.2
Outdoor Fan Motor W	85
Indoor Fan Motor RLA	4.0
Indoor Fan Motor W	560
System Power Input @ Cooling (W)	5400(1160 ~ 6120)
System Power Input @ Heating (W)	4700(795 ~5150)
MCA: Min. circuit amps (A)	MOC: Max. over current protection (A)
RLA: Rated load amps (A)	W: Fan motor rated output (W)

PIPING

Throttle type(Indoor)	N/A
Throttle type(Outdoor)	EXV+Throttle valve
Liquid Size	9.52mm(3/8in)
Gas Size	19mm(3/4in)
Max. Piping Length(ft/m)	246.00(75)
Max. Height Difference(ft/m)	98.40(30)
Max. Pre-charged Length(ft/m)	24.6(7.5)
Refrigerant Pre-charged Amount(oz/kg)	151.68(4.30)
Additional Charge (oz/ft)/(g/m)	0.32(30)
Connection Method	Flared

Air outlet dimensions**Air inlet dimensions**


(unit: inch/mm)

MODEL	OUTLINE DEMENSION				AIR OUTLET OPENING SIZE		AIR RETURN OPENING SIZE		SIZE OF MOUNTED LUG	
	A	B	C	D	E	F	G	H	I	J
9K/12K	27.6/700	9.6/245	29.5/750	31.3/795	20.7/527	7.0/178	23.3/592	8.3/212	29.1/740	25.2/640
18K/24K	39.4/1000	9.6/245	29.5/750	31.3/795	32.6/827	7.0/178	35.1/892	8.3/212	40.9/1040	25.2/640
36K/48K	47.2/1200	11.8/300	29.5/750	31.3/795	40.4/1027	9.2/233	43.0/1092	10.5/267	48.8/1240	25.2/640
55K/60K	55.1/1400	14.9/380	31.5/800	33.3/845	48.1/1223	12.6/320	50.1/1272	13.0/330	56.7/1440	26.3/668


Installation place

The distance between the mounted indoor unit should meet the specifications illustrated in the following diagram.


1) Ceiling-mounted



2) Wall-mounted




Outdoor Unit Dimensions



Outdoor Unit Clearances





REQUIRED CLEARANCE





*1 20 in. (500 mm) or more when front and sides of the unit are clear




*2 When any 2 sides of left, right and rear of the unit are clear

Fan performance





Constant air volume



Features

- Compatible with both horizontal and vertical installation
- Static pressure up to 0.8 in.w.g(for all models)
- Static pressure setting stages: 8
- Refrigerant leakage detection sensor
- Constant airflow
- Built-in pump
- i-clean
- Fan speed stages: 1~100%
- WiFi capability: through wired controller with built-in WiFi
- OTA(by using wired controller 120N(X6W))
- 2-pin connector(HA/HB) for programmable wired controller
- Multiple control options available:
 - Two way communication wired controller:120N(X6)
 - Two way communication wired controller with built-in WiFi:120N(X6W)
 - Infrared wired controller: 120L
 - Wireless remote controller
 - Third-Party 24V Thermostat*

*24V interface is required.